

CLAIMS

1. A stiffener to provide stiffening support to one of a thin-core and coreless substrate of an integrated circuit printed circuit board (IC-PCB) carrier package.
2. A stiffener as claimed in claim 1, the IC-PCB carrier package being one of a flip chip pin grid array (FC-PGA) and a flip chip ball grid array (FC-BGA) carrier package.
3. A stiffener as claimed in claim 1, the stiffener is substantially made of at least one of a metal-like, plastic-like, glass-like and ceramic-like material, is one of a molded, stamped, etched, extruded and deposited stiffener, and is capable of withstanding high temperatures of at least one of an IC die bonding operation and normal IC operation.
4. A stiffener as claimed in claim 1, the stiffener being planar for mounting to a die-side major planar surface of the substrate.
5. A stiffener as claimed in claim 1, the stiffener having an internal window therein to provide clearance for at least one of a die, under-fill, die side components (DSC), and integrated heat spreader (IHS).
6. A stiffener as claimed in claim 1, the stiffener being a multi-part stiffener.

7. A stiffener as claimed in claim 1, the stiffener having an above-substrate-plane height when mounted, which is less than or equal to an above-substrate-plane height, when mounted, of one of: an IC-die, and a combination of an IC-die with an integrated heat spreader (IHS).

8. A stiffener as claimed in claim 1, the stiffener having a top surface above a substrate-plane when mounted, which is substantially co-planar with, when mounted, a top surface of one of: an IC-die, and a combination of an IC-die with an integrated heat spreader.

9. A stiffener as claimed in claim 8, the stiffener being adapted to co-support a heat sink, with one of: an IC-die, and a combination of an IC-die with an integrated heat spreader (IHS).

10. A stiffener as claimed in claim 1, where if a main body of the stiffener is electrically conductive, the stiffener further includes an insulator to electrically insulate electrical members on stiffener-opposing areas of the substrate.

11. A stiffener as claimed in claim 1, the stiffener being an edge stiffener for mounting to minor-planar side-surfaces of the substrate.

12. A stiffener as claimed in claim 1, the edge stiffener having a non-flat cross section which is adapted to mate with the side-surfaces of the substrate.

13. A stiffener as claimed in claim 1, where the edge stiffener is adapted to be pre-attached to the substrate by an IC-PCB carrier package manufacturer.
14. A thin-core or coreless integrated circuit printed circuit board (IC-PCB) carrier package comprising: a stiffener to provide stiffening support to one of a thin-core and coreless substrate of the IC-PCB carrier package.
15. An IC-PCB carrier package as claimed in claim 14, the IC-PCB carrier package being one of a flip chip pin grid array (FC-PGA) and a flip chip ball grid array (FC-BGA) carrier package.
16. An IC-PCB carrier package as claimed in claim 14, where the stiffener is substantially made of at least one of a metal-like, plastic-like, glass-like and ceramic-like material, is one of a molded, stamped, etched, extruded and deposited stiffener, and is capable of withstanding high temperatures of at least one of an IC die bonding operation and normal IC operation.
17. An IC-PCB carrier package as claimed in claim 14, the stiffener being planar and mounted to a die-side major planar surface of the substrate.
18. An IC-PCB carrier package as claimed in claim 14, the stiffener having an internal window therein to provide clearance for at least one of a die, under-fill, die side components (DSC), and integrated heat spreader (IHS).

19. An IC-PCB carrier package as claimed in claim 14, the stiffener being a multi-part stiffener.

20. An IC-PCB carrier package as claimed in claim 14, the stiffener having an above-substrate-plane height, which is less-than or equal to an above-substrate-plane height, when mounted, of one of: an IC-die, and a combination of an IC-die with an integrated heat spreader (IHS).

21. An IC-PCB carrier package as claimed in claim 14, the stiffener having a top surface above a substrate-plane, which is substantially co-planar with, when mounted, a top surface of one of: an IC-die, and a combination of an IC-die with an integrated heat spreader.

22. An IC-PCB carrier package as claimed in claim 21, the stiffener being adapted to co-support a heat sink, with one of: an IC-die, and a combination of an IC-die with an integrated heat spreader (IHS).

23. An IC-PCB carrier package as claimed in claim 14, where if a main body of the stiffener is electrically conductive, the stiffener further includes an insulator to electrically insulate electrical members on stiffener-opposing areas of the substrate.

24. An IC-PCB carrier package as claimed in claim 14, the stiffener being an edge stiffener mounted to minor-planar side-surfaces of the substrate.

25. An IC-PCB carrier package as claimed in claim 14, the edge stiffener having a non-flat cross section which is mated with the side-surfaces of the substrate.

26. An IC-PCB carrier package as claimed in claim 14, where the edge stiffener is pre-attached to the substrate by an IC-PCB carrier package manufacturer.

27. A packaged integrated circuit (IC) comprising:
a thin-core or coreless integrated circuit printed circuit board (IC-PCB) carrier package comprising a stiffener to provide stiffening support to one of a thin-core and coreless substrate of the IC-PCB carrier package.

28. A packaged IC as claimed in claim 27, the IC-PCB carrier package being one of a flip chip pin grid array (FC-PGA) and a flip chip ball grid array (FC-BGA) carrier package.

29. A packaged IC as claimed in claim 27, where the stiffener is substantially made of at least one of a metal-like, plastic-like, glass-like and ceramic-like material, is one of a molded, stamped, etched, extruded and deposited stiffener, and is capable of withstanding high temperatures of at least one of an IC die bonding operation and normal IC operation.

30. A packaged IC as claimed in claim 27, the stiffener being planar and mounted to a die-side major planar surface of the substrate.

31. A packaged IC as claimed in claim 27, the stiffener having an internal window therein to provide clearance for at least one of a die, under-fill, die side components (DSC), and integrated heat spreader (IHS).

32. A packaged IC as claimed in claim 27, the stiffener being a multi-part stiffener.

33. A packaged IC as claimed in claim 27, the stiffener having an above-substrate-plane height, which is less-than or equal to an above-substrate-plane height, when mounted, of one of: an IC-die, and a combination of an IC-die with an integrated heat spreader (IHS).

34. A packaged IC as claimed in claim 27, the stiffener having a top surface above a substrate-plane, which is substantially co-planar with, when mounted, a top surface of one of: an IC-die, and a combination of an IC-die with an integrated heat spreader.

35. A packaged IC as claimed in claim 34, the stiffener being adapted to co-support a heat sink, with one of: an IC-die, and a combination of an IC-die with an integrated heat spreader (IHS).

36. A packaged IC as claimed in claim 27, where if a main body of the stiffener is electrically conductive, the stiffener further includes an insulator to electrically insulate electrical members on stiffener-opposing areas of the substrate.

37. A packaged IC as claimed in claim 27, the stiffener being an edge stiffener mounted to minor-planar side-surfaces of the substrate.

38. A packaged IC as claimed in claim 27, the edge stiffener having a non-flat cross section which is mated with the side-surfaces of the substrate.

39. A packaged IC as claimed in claim 27, where the edge stiffener is pre-attached to the substrate by an IC-PCB carrier package manufacturer.

FIG. 1
FIG. 2
FIG. 3
FIG. 4
FIG. 5
FIG. 6
FIG. 7
FIG. 8
FIG. 9
FIG. 10
FIG. 11
FIG. 12
FIG. 13
FIG. 14
FIG. 15
FIG. 16
FIG. 17
FIG. 18
FIG. 19
FIG. 20
FIG. 21
FIG. 22
FIG. 23
FIG. 24
FIG. 25
FIG. 26
FIG. 27
FIG. 28
FIG. 29
FIG. 30
FIG. 31
FIG. 32
FIG. 33
FIG. 34
FIG. 35
FIG. 36
FIG. 37
FIG. 38
FIG. 39
FIG. 40
FIG. 41
FIG. 42
FIG. 43
FIG. 44
FIG. 45
FIG. 46
FIG. 47
FIG. 48
FIG. 49
FIG. 50
FIG. 51
FIG. 52
FIG. 53
FIG. 54
FIG. 55
FIG. 56
FIG. 57
FIG. 58
FIG. 59
FIG. 60
FIG. 61
FIG. 62
FIG. 63
FIG. 64
FIG. 65
FIG. 66
FIG. 67
FIG. 68
FIG. 69
FIG. 70
FIG. 71
FIG. 72
FIG. 73
FIG. 74
FIG. 75
FIG. 76
FIG. 77
FIG. 78
FIG. 79
FIG. 80
FIG. 81
FIG. 82
FIG. 83
FIG. 84
FIG. 85
FIG. 86
FIG. 87
FIG. 88
FIG. 89
FIG. 90
FIG. 91
FIG. 92
FIG. 93
FIG. 94
FIG. 95
FIG. 96
FIG. 97
FIG. 98
FIG. 99
FIG. 100